

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E146589  
**Report Reference** E146589-20001010  
**Issue Date** 2020-APRIL-21

**Issued to:** BARKSDALE INC  
3211 FRUITLAND AVE  
LOS ANGELES CA 90058

**This certificate confirms that  
representative samples of**

TELEMETERING EQUIPMENT FOR USE IN HAZARDOUS  
LOCATIONS

See Addendum page for models

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:**

UL 122701, Requirements for Process Sealing Between  
Electrical Systems and Flammable or Combustible Process  
Fluids  
ANSI/ISA 12.27.01, Explosive Atmospheres – Part 28:  
Protection of equipment and transmission systems using  
optical radiation


**Additional Information:**

See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




# CERTIFICATE OF COMPLIANCE

**Certificate Number** E146589  
**Report Reference** E146589-20001010  
**Issue Date** 2020-APRIL-21

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Pressure transmitter, Models 443 and 446 followed by -H3, -H3-E, -H5, -H5E, -H6, -H6-E, -T4, -T4-E, -T5, -T5-E, -T8, -T8-E, followed by -01, -03, -04, -05, -06, -07, -08, -10, -11, -12, -13, -14, -15, -16, -17, -18, -19, -21, -22, -23, or -25, may be followed by -Z10, -Z11, -Z12, -Z15, -Z16, -Z17, or -Z18, -W, or -4 digits, may be followed by A, may be followed by P1 through P10, or by Q1 through Q999; intrinsically safe for use in Class I, Division 1, Groups A, B, C and D; Class II, Division 1, Groups E, F, and G Hazardous Locations when installed in accordance with Control Drawings No. 272148 or 272147 respectively, provided with process seal, single seal type up to 6,834 psi.

Pressure transmitter, Models 443 and 446 followed by -H5, -H5E, -T8, -T8-E followed by -01, -03, -04, -05, -06, -07, -08, -10, -11, -12, -13, -14, -15, -16, -17, -18, -19, -21, -22, -23 or -25, may be followed by -Z10, -Z11, -Z12 -Z15, -Z16, -Z17, or -Z18, W, or -4 digits, may be followed by A, may be followed by P1 through P10, or by Q1 through Q999; non-incendive for use in Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G Hazardous Locations, provided with process seal, single seal type up to 6,834 psi.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

